

**PRODUCT REQUIREMENT SHEET**

See LV 75-032

<b>MEASURING VOLTAGE</b>	240V (stabilisation 3 min.)
<b>MEASURING POSITION</b>	Horizontal
<b>LIFE TEST POSITION</b>	Horizontal
<b>BURNING POSITION</b>	P15
<b>SWITCHING CYCLE</b>	Continuous
<b>AGEING</b>	1h at rated voltage

	VALUE UNIT	TOLERANCE
<b>WATTAGE</b>	1000W	± 6 %
<b>LIFE</b>	5000 h	average
<b>COLOR TEMPERATURE</b> Clear lamp Lamp with reflector	2500 K NA	± 100 K
<b>FLUX (HeLeN lamp)</b>	NA	
<b>WEIGHT</b>	35 g	

1	0833	2	0833	3	0000	4		5		6		7		8	
SUPERSEDES :		HALOGEN LAMP						9245 178 43800			08/12/2010				
9245 178 43800		INFRARED INDUSTRIAL						0833/000							
0833/000 p. 190-2		1000T3 1000W 230-250V TRL													
Of 16/06/2004		REF. : PDM IRK 2010-053		DOCUMENTATION	UNIT mm	PROJ EUROP	2 SH	SH	190-2	10			A4		
NOM : J.P. CHARLIER		VALIDATION : A. PICHARD						DR. FISCHER Europe							
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.															